

The Energy Flux Method for Reverberation: Modeling and Inversion

Ji-Xun Zhou

School of Mechanical Engineering

Georgia Institute of Technology

Atlanta, GA 30332-0405

phone: (404) 894-6793 fax: (404) 894-7790 email: jixun.zhou@me.gatech.edu

Award Number: N00014-11-1-0063

LONG-TERM GOALS

The long-term goals of this work are: (1) to develop a reverberation model for predicting the reverberation level and the echo-to-reverberation ratio in shallow water (SW), and (2) to characterize the seabed scattering in a frequency band of 100-3000 Hz from long-range broadband reverberation measurements.

OBJECTIVES

The scientific objectives of this work include: (1) to integrate the energy flux method for SW reverberation with physics-based seabed scattering models for reverberation prediction and inversion, and (2) to analyze the mechanisms of low-frequency (LF) seabed scattering, obtained from reverberation data and the Biot seabed geo-acoustic model.

APPROACH

(1) The energy flux (angular power spectrum) method for reverberation, based on the W.K.B approximation to the normal-mode solution [1], is integrated with physics-based seabed scattering models [2] to get SW reverberation expressions; (2) The effective Biot acoustic model for sandy and sand-silt mixture bottoms, derived from broadband LF field measurements at many locations [3], is used to model two-way sound propagation in the reverberation; (3) The broadband reverberation data are used to characterize the seabed scattering; (4) The LF seabed scattering cross-sections, derived from the long-range reverberation data, will be used to estimate the geo-physical parameters of the seabed roughness and the sediment inhomogeneity, and to analyze LF seabed scattering mechanisms.

RESULTS

(1) The energy flux method for SW reverberation is integrated with the rough bottom scattering (RBS) model and the sediment volume scattering (SVS) model. This integration directly and intuitively results in general expressions for SW reverberation in the angular domain and in the modal domain. The resultant reverberation expressions can conveniently be used for predicting SW reverberation for the Pekeris waveguide or non-Pekeris waveguide, respectively. The reverberation intensity in shallow water, derived from the energy flux method, can be expressed by a summation over normal modes:

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 30 SEP 2013		2. REPORT TYPE		3. DATES COVERED 00-00-2013 to 00-00-2013	
4. TITLE AND SUBTITLE The Energy Flux Method for Reverberation: Modeling and Inversion				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Georgia Institute of Technology,School of Mechanical Engineering,Atlanta,GA,30332				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 5	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

$$R(r, z; z_0) = \frac{c_w \tau_0}{\pi r} e^{-2\alpha_w r} \sum_m \sum_n \frac{k_m (k_m - k_{m+1})^2 \exp(-2\beta_m r)}{\left[k_w^2(z_0) D(z_0) + k_w^2(z_0) - k_m^2 \right]^{1/2} \left[k_w^2(h) D(h) + k_w^2(h) - k_m^2 \right]^{1/2}} \\ \times \sigma(\theta_m, \theta_n) \times \frac{k_n (k_n - k_{n+1})^2 \exp(-2\beta_n r)}{\left[k_w^2(h) D(h) + k_w^2(h) - k_n^2 \right]^{1/2} \left[k_w^2(z) D(z) + k_w^2(z) - k_n^2 \right]^{1/2}} \quad (1)$$

where k_n is the longitudinal wave number of the n th mode, and β_n is the modal attenuation coefficient. r is distance, and h is the water depth; z_0 is the source depth and z is the receiver depth. α_w is the water absorption coefficient. $\sigma[\theta_m, \theta_n]$ is the bottom scattering cross section per unit area; $\theta_m(h)$ is the incident grazing angle of mode m at the bottom; and $\theta_n(h)$ is the scattering angle of mode n .

$k_w(z) = 2\pi f / c_w(z)$ is the wave number in the water. τ_0 is the signal pulse duration. $D(z)$ is a minor modification factor for overcoming a problem when a receiver is near a turning point,

$$D(z) = 0.875 \left| \frac{1}{\pi f} \frac{dc_w(z)}{dz} \right|^{2/3} \quad (2)$$

For arbitrary velocity profiles, Eq. (1) can be used to calculate SW long-range reverberation intensity by using the classic cross sections of seabottom scattering and any available normal-mode code. This only requires two parameters: real and imaginary parts of the modal eigenvalue k_m , and β_m .

(2) The integration of the energy flux method with seabed scattering models also results in a simple relationship between the classic boundary scattering cross sections and the modal scattering matrix in SW waveguides:

$$MSM(m, n) = \frac{\Phi_m^2(h)}{|1 + V_{ww}(\theta_m)|^2} \times \sigma(\theta_m, \theta_n) \times \frac{\Phi_n^2(h)}{|1 + V_{ww}(\theta_n)|^2} \quad (3)$$

Here $MSM(m, n)$ is defined as the modal scattering matrix in the SW waveguide between an incident mode m and a scattering mode n . $\Phi_m(h)$ is the amplitude of m^{th} mode at the water-bottom interface where the modal angle $\theta_m = \cos^{-1}[k_m / k_w(h)]$. $\sigma(\theta_m, \theta_n)$ can be either the RBS cross section or the SVS cross section. V_{ww} is the sound reflection coefficient with the scripts ww added to indicate that the incident and reflected fields are both in the water.

(3) The data-model comparisons show that the reverberation can almost be equally well predicted by using the RBS model and SVS model. Thus, the scattering parameters for the RBS model and the SVS model have been inverted from reverberation data. However, the reverberation level as a function of time, $RL(t)$, at one single frequency cannot uniquely determine the seabed scattering parameters. As an example, Figure 1 shows the internal parameter coupling for the RBS model between the spectral exponent γ_2 and the spectral strength ω_2 : three different pairs of γ_2 and ω_2 would result in an identical $RL(t)$. An increase (decrease) in γ_2 can be compensated for by an increase (decrease) in ω_2 .

(4) The wideband reverberation data as a function of frequency, $RL(f)$, at given reverberation times can uniquely determine a set of the bottom roughness spectra or the sediment volume scattering cross

section. As an example, Figure 2 shows that the wideband reverberation data are used to uniquely invert a set of seabed scattering parameters for the RBS and SVS models. The bottom roughness spectrum and the sediment volume scattering cross section, inverted from the broadband long-range reverberation data at the ASIAEX site, exhibit different characteristics from those commonly used in HF. For the HF, the roughness spectrum exponent is restricted to the range of $2 \leq \gamma_2 \leq 4$ with a mean value of 3.0; the LF roughness spectrum exponent from long-range reverberation data has smaller values with a mean value around $\gamma_2 \approx 1.3$. The HF sediment volume scattering cross section σ_v is generally assumed to have linear frequency dependence. However, Figure 3 shows that the σ_v , inverted from long-range reverberation data, exhibits much stronger frequency dependence in the 150-2500 Hz range: $\alpha_v = (0.00238 \pm 0.00004)f^{(3.805 \pm 0.021)}$, here f is frequency in a unit of kHz.

(5) All the LF seabed scattering parameters for the RBS model and the SVS model, inverted from the long-range (3 to 12 s) reverberation data, are listed in Table I. The standard deviations between the measured reverberation data and the theoretical predictions for all the frequencies are also listed in Table I. These seabed scattering parameters for the RBS model and the SVS model may be used for future analyzing which one (or both) is dominating LF scattering mechanism at low grazing angles. In Figure 2 and Table I, α_p (in a unit of dB/m) is the sound attenuation in the sea bottoms that obeys the Biot model [3].

IMPACT/APPLICATIONS

The resultant reverberation expressions with the physics-based seabed scattering models can conveniently be used to predict the SW reverberation and to characterize the LF seabed scattering.

RELATED PROJECTS

NONE

REFERENCES

1. J.X. Zhou, "The Analytical method of angular power spectrum, range and depth structure of the echo-to-reverberation ratio in shallow water Sound Field," (Chinese) ACTA ACUSTICA, **5** (2), 86-99 (1980).
2. D.R. Jackson and M.D. Richardson, <High-frequency Seafloor Acoustics>, 616 pages, Springer, 2007.
3. J.X. Zhou, X.Z. Zhang, and D.P. Knobles, "Low-frequency geoacoustic model for the effective properties of sandy seabottoms," J. Acoust. Soc. Am., **125**, 2847-2866 (2009).

PUBLICATIONS

1. J.X. Zhou and X. Z. Zhang, "Shear wave velocity and attenuation in the upper layer of ocean bottom from long-range acoustic field measurements," J. Acoust. Soc. Am., **132**(6), 3698-3705, Dec. 2012. [published, refereed].
2. J.X. Zhou and X.Z. Zhang, "Integrating the energy flux method for reverberation with physics-based seabed scattering models: Modeling and inversion," J. Acoust. Soc. Am., **134** (1), 55-66, July 2013. [published, refereed].




Fig. 1. Internal parameter coupling between the spectral exponent γ_2 and the spectral strength ω_2 for the RBS model. Three different pairs of γ_2 and ω_2 result in a identical $RL(t)$. An increase in γ_2 can be compensated for by an increase in ω_2 .




Fig. 2. Wideband reverberation data at the ASIAEX site are used to invert a set of seabed scattering parameters for the RBS and SVS models.




Fig. 3 The sediment volume scattering cross section, inverted from long-range reverberation data at the ASIAEX site, exhibits strong frequency dependence: $\alpha_v = 0.00238 f^{3.805}$ (f in kHz)

Table I. The LF seabed scattering parameters for the RBS model and the SVS model, inverted from long-range (3 to 12 s) reverberation data at the ASIAEX site

Models Rev. time and rang-to-depth ratio		RBS : Bottom roughness spectrum $W(\Delta K) = \omega_2 / (\Delta K)^{\gamma_2}$			SVS: Volume scattering cross section: $\sigma_v = \sigma_2^* \alpha_p^{n_v}$		
		γ_2	$\omega_2 \times 10^{-5}$	$std_{RBS}(dB)$	σ_2^*	n_v	$std_{SVS}(dB)$
$t_R = 3.0$	$r/h = 22$	1.6	4.9	1.419	0.014	1.9	1.603
4.0	29	1.4	3.2	1.192	0.015	2.0	1.348
5.0	37	1.3	2.6	1.719	0.017	2.1	1.874
6.0	44	1.3	2.5	1.473	0.014	2.0	1.668
7.0	52	1.2	2.0	1.547	0.016	2.1	1.725
8.0	59	1.2	2.1	1.672	0.017	2.1	1.855
10.0	73	1.2	2.4	1.191	0.020	2.1	1.243
12.0	88	1.2	2.9	1.513	0.024	2.1	1.578